

OCTOBER 30, 1981

TYPE "ARAM" MULTIPLE SHEATH CABLES

SEE RATINGS
BELOW

Dual expanded polyethylene-PVC insulated 22 gauge untinned annealed copper conductor pairs stranded, cabled and covered with a bonded aluminum-PVC (ALVYN) sheath, conductor insulation and unit binders follow the standard color code for plastic insulated multiplex sheath cables.

DC Resistance: 182 OHMS per loop mile at 68°F.

Mutual Capacitance: 83 mF per mile at 1000 Hz.

Insulation Resistance: More than 15000 megohm miles.

Dielectric Strength: More than 1500 volts dc between conductors. In excess of 5000 volts dc between each conductor and sheath.

Code	No. of Pairs	Outside Diameter (Inches)	Weight Per Ft. (Pounds)	Max. Length (Feet) Reel Size			Rating
				416	417	420	
ARAM-150	150	1.27	0.91	2260	2910	5090	A.T.&T.Co.Std.
ARAM-200	200	1.43	1.17	1850	2540	5080	" "
ARAM-300	300	1.70	1.70	1190	1690	2890	" "
ARAM-400	400	1.93	2.20	950	1430	2510	" "
ARAM-600	600	2.32	3.26	680	900	1660	" "
ARAM-900	900	2.79	4.82	440	620	1240	" "