

OCTOBER 30, 1981

TYPE "ARTM" MULTIPLE SHEATH CABLES

SEE RATINGS
BELOW

Dual expanded polyethylene-PVC insulated 26 gauge untinned annealed copper conductor pairs stranded, cabled, and covered with a bonded aluminum-PVC (ALVYN) sheath. Conductor insulation and unit binders follow the standard color code for plastic insulated multiple sheath cables.

DC Resistance: 464 OHMS per loop mile at 68°F.

Mutual Capacitance: 83 nF per mile at 1000 Hz.

Insulation Resistance: More than 15000 megohm miles.

Dielectric Strength: More than 1000 volts dc between conductors. In excess of 5000 volts dc between each conductor and sheath.

Code	No. of Pairs	Outside Diameter (Inches)	Weight Per Ft. (Pounds)	Max. Length (Feet) Reel Size			Rating
				416	417	420	
ARTM-300	300	1.17	0.71	2690	3820	6540	A.T.&T.Co.Std.
ARTM-400	400	1.33	0.92	1990	3050	5710	" "
ARTM-600	600	1.58	1.34	1470	2170	3800	" "
ARTM-900	900	1.88	1.96	970	1460	2670	" "
ARTM-1200	1200	2.14	2.58	740	1190	2060	" "
ARTM-1800	1800	2.57	3.81	500	700	1370	" "
ARTM-2400	2400	2.92	5.04	340	500	1000	" "
ARTM-2700	2700	3.09	5.65	290	440	910	" "
ARTM-3000	3000	3.25	6.27	290	440	910	" "
ARTM-3600	3600	3.53	7.50	290	340	680	" "