

**MANUAL OUTGOING TRUNK TEST FRAME
AND OUTGOING TRUNK TEST JACK BAY
EQUIPMENT DESIGN REQUIREMENTS
NO. 5 CROSSBAR, CROSSBAR TANDEM AND
NO. 4 TYPE TOLL SWITCHING SYSTEMS**

1 GENERAL

1.001 This addendum supplements Section 817-705-150, 819-710-150, and 818-708-150, Issue 10.

1.002 This addendum is issued:

(a) To rate ED-92266-11, Group 53 and 58 Mfr Disc. per SD-68203-01, Issue 15D which rated the tone and probe feature Mfr Disc.

(b) To add ED-92266-11, Group 67 and 68 and revise Group 62 per SD-68203-01, Issue 15D which provides test and make-busy appearances for three new toll switching outgoing trunks used for completing INWATS calls to No. 3 ACD.

◆ (c) To add ED-92266-10, Group 47 for testing outgoing trunks SD-28034-01 to remote CAMA positions. ◆

4. EQUIPMENT

The following changes apply to Part 4 of the section:

(a) ED-92266-11, Groups 53 and 58—rerated

(b) ED-92266-11, Group 62—revised

(c) ED-92266-11, Groups 67 and 68—added

◆ (d) ED-92266-10, Group 36—revised

(e) ED-92266-10, Group 47—added

(f) J98501A-()—Lists 41, 42, 43, 44—added

(g) J98501R-()—Lists 2, 3—added. ◆

◆ *Under ED-92266-10*

Change: Group 36

To Read:

Group 36—Jack and jack mountings (designation strip omission of jack space) per Fig. AK and cords in accordance with SD-95849-01, Fig. 3 and option Z, required in addition to group 1 when testing outgoing trunks SD-96481-01 to remote CAMA positions. (See Group 47.)

Add:

Group 47—Jacks and jack mountings (designation strip omission of jack space) per Fig. AT and cords in accordance with SD-95849-01, Fig. 3 and option Y, required in addition to group 1 when testing outgoing trunk SD-28034-01, to remote CAMA positions. (See Group 36.) ◆

Under ED-92266-11

Rate: Groups 53 and 58 Mfr Disc.

Change: Group 62

To Read:

Group 62—Sixty jack circuits (designation strips and omission of jack spaces) per Fig. BQ required in addition to group 2 or group 5 for outgoing trunks to CAMA positions (SD-68203-01, Fig. 2 and 8) or for 2-wire RVB outgoing trunks to No. 3 ACD (SD-68203-01, Fig. 9).

NOTICE

Not for use or disclosure outside the
Bell System except under written agreement

Printed in U.S.A.

J98501, ISS 10; ADD. 2
SECTION 817-705-150, 818-708-150, 819-710-150

Add:

Group 67—Forty jack circuits (designation strips and omission of jack spaces) per Fig. BT required in addition to group 2 or group 5 for 4-wire RVB outgoing trunks to No. 3 ACD (SD-68203-01, Fig. 10).

Group 68—Forty jack circuits (designation strips and omission of jack spaces) per Fig. BU required in addition to group 2 or group 5 for 4-wire E and M outgoing trunks to No. 3 ACD (SD-68203-01, Fig. 11).

List 43—Light emitting diodes required in addition to list 22 per SD-95849-01, Fig. 2 option Y only for testing outgoing trunks SD-28034-01 to remote CAMA positions.

List 44—Light emitting diodes required in addition to list 22 per SD-95849-01, Fig. 2 option Z only, for testing outgoing trunks SD-96481-01 to remote CAMA positions.

Under J98501R-()

Add:

List 2—Apparatus and wiring per SD-95849-01, Fig. 1, option Z only, required in addition to list 1 for testing outgoing trunks SD-96481-01 to CAMA positions.

List 3—Apparatus and wiring per SD-95849-01, Fig. 1, option Y only, required in addition to list 1 for testing outgoing trunks SD-28034-01 to CAMA positions. (Tandem only.) ♦

♦ **Under J98501A-()**

Add:

List 41—Wiring and equipment per SD-95476-01, Fig. 26 required in addition to list 1 for ATMS transmission measurements and remote ROTL control via selected trunks.

List 42—Designation strip and lamp socket mounting required when list 43 is provided.

Bell Telephone Laboratories, Incorporated

Dept 55213
WE Dept 45240